

SOLAR STREET LIGHT

YL-SL002

Integrated Solar Light Pole

Aluminum construction | 3-10 m range | 10-100 W

POLE MATERIAL

6063-T6 aluminum alloy

SURFACE FINISH

Electrostatic powder coating

SOLAR PANEL

Monocrystalline silicon

BATTERY

Lithium iron phosphate (LiFePO4)

LIGHTING MODE

Constant illumination for 12 hours

AUTONOMY

1-2 rainy days



WARRANTY

3 YEARS

Model Selection & Technical Data

All variants use model code YL-SL002 and a 4000 K light source.

Pole Height	Model	LED Power	Color Temperature
10 m	YL-SL002	100 W	4000 K
9 m	YL-SL002	100 W	4000 K
8 m	YL-SL002	80 W	4000 K
7 m	YL-SL002	80 W	4000 K
6 m	YL-SL002	40 W	4000 K
5 m	YL-SL002	40 W	4000 K
4 m	YL-SL002	20 W	4000 K
3 m	YL-SL002	10 W	4000 K

Standard Configuration

POLE

6063-T6 aluminum alloy

SURFACE

Electrostatic powder coating

SOLAR PANEL

Monocrystalline silicon

BATTERY

Lithium iron phosphate (LiFePO4)

RAINY-DAY BACKUP

1-2 days

OPERATING MODE

Constant illumination for 12 hours

WARRANTY

3 years

Contact Us for a Project Quote

Custom heights, lighting power and project requirements are welcome.

PHONE / WHATSAPP / WECHAT

+86 189 3301 1151

EMAIL

quote@fsyaolong.com

www.yaolonglightpole.com



WHATSAPP



WECHAT